

DC-T1232WR



CÁMARA IP TIPO BALA IP66 RES. 2 MEGAPIXELES COMPRESIÓN H.264/MJPEG 42 LEDS IR (30 METROS) LENTE VF MOTORIZADO: 3.3-10mm IVA: DETECTOR DE MOVIMIENTO / ANTI-MANIPULACION / TRIPZONE 12V DC / POE / ONVIF S / DIRECT IP

Rating: Not Rated Yet
[Ask a question about this product](#)

Manufacturer: [IDIS](#)

Description

Full HD IR Bullet Camera DC-T1232WR

- Easy installation with DirectIP NVR
- Full HD (1080p) resolution
- Motorized Varifocal(3.3 - 10mm)
- Vandal proof / IP66 supports
- PoE/Ether 802.3af class II, 12V DC
- Day&night (ICR)
- IR LED (Distance : 30m)
- 3-axis mechanical design for installation
- Supports ONVIF



SPECIFICATIONS

Image Sensor	1/3" CMOS
Max Resolution	1920 x 1080
Scanning Mode	Progressive Scan
Min. ILL	Minimum Illumination
Focal Length	3.3-10mm
Aperture	F1.2, F1.5
Max. Control	DC Auto Iris
Angle of Field of View	Horiz: 90°(H), 52°(V), 114°(D) Max: 132°(H), 18°(V), 38°(D)
Max. Resolution	1080P, 720P, 4CIF, 2CIF, 256K, 128K, 64K, 32K, 16K, 8K, 4K, 2K, 1K, 512, 256, 128, 64, 32, 16, 8, 4, 2, 1
IR Mode	2D, 3D
Distance Range	74.3M
Distance Range Speed	Auto Manual (300 - 1,800KHz, Auto Focus, Slow Shutter(1/5, 1/10))
Day & Night	IR cut filter with auto switch
IP Protection (IP66)	200-250mm
Image Setting	Contrast, Saturation, White Balance, Sharpness
Light Noise Reduction	Color Noise (2D)
Backlight Compensation	On / Off / HSB/C
Blurring Filter	Horizontal / Vertical / Reset
Image Stabilizer	14 Zones
Image Backup	Video Motion Detection, Action, Tampering Alarm, Trip Zone
Video Size	1,280
Protocol	DirectIP Mode
Video Compression	H.264, H.265, MJPEG
Video Control	H.264, H.265, H.265
Max. Video Size	30Mbps / 1080P x 1080P
Audio Compression	-
Audio Code	-
IP Camera Protocol	DirectIP
Supported Resolution	1920x1080, 1280x720, 1080x720, 704x480, 640x480, 320x240
Multi Video Streaming	Quadriplex streaming
Network Protocols	Direct IP Protocol
Security	SSL, Encryption
Remote Access Client	DirectIP NVR connection
Alarm	1080P, 720P, 4CIF, 2CIF, 256K, 128K, 64K, 32K, 16K, 8K, 4K, 2K, 1K, 512, 256, 128, 64, 32, 16, 8, 4, 2, 1
Alarm Storage	1080P, 720P, 4CIF, 2CIF, 256K, 128K, 64K, 32K, 16K, 8K, 4K, 2K, 1K, 512, 256, 128, 64, 32, 16, 8, 4, 2, 1
Image Detail	Motion Detection, Tampering, TripZone
Anti-Masking (PoE & Net)	Anti-Spoof (IP Spoof)
Event Notification	Remote NVR Email with Image
Audio In	-
Audio Out	-
Audio Format	-
Audio Compression	-
Audio Code	-
Audio Storage	-
Audio Detail	-
Audio In	-
Audio Out	-
Audio Format	-
Audio Compression	-
Audio Code	-
Audio Storage	-
Audio Detail	-
Power Source	12VDC, PoE (IEEE 802.3af class II)
Power Consumption	5.5W
Approval	FCC, CE, RoHS
Dimensions	87.5 (mm) x 29.5 (mm) x 82.5 (mm) (11.63" x 3.74" x 3.25")
Weight	115 (g) (4.06 (oz))

DIMENSIONS



Reviews

There are yet no reviews for this product.