

# DR-2104P



NVR DE 4 CANALES (DIRECT IP) 4 CANALES POE / ONVIF

Rating: Not Rated Yet  
[Ask a question about this product](#)

Manufacturer: [IDIS](#)

## Description



DirectIP™ 2100 Series 4 Channel Full HD Recorder  
**DR-2104P**




### KEY FEATURES

- Total Incoming throughput 84Mbps
- Up to 120fps Full HD real-time recording
- Up to 120fps live display
- Easy to install, set-up and play with DirectIP™ cameras
- Built-in 4 Channel PoE Switch
- Expandable up to 6TB
- Supports one click network configuration through FEN Service
- Supports third party cameras (Axis, Panasonic, ONVIF™)


### SPECIFICATIONS

<b>Video</b>	4 IP camera
<b>Video Type</b>	H.264
<b>Max. Incoming Throughput</b>	84Mbps
<b>Supports Camera</b>	DirectIP™ Axis, Panasonic, ONVIF™
<b>Max. Storage</b>	160GB, 1 YJA, DVD
<b>Display Resolution</b>	1920 x 1080, 1600 x 1200, 1440 x 1056, 1024 x 768
<b>Display Format</b>	16:9, 4:3
<b>Max. Throughput</b>	24Mbps, 120fps@1/2 HD
<b>Recording Resolution</b>	Up to 1080P depending on IP Camera
<b>Compression</b>	H.264
<b>Recording Mode</b>	Time-lapse, Event, Pre-event, Post
<b>Trigger Events</b>	Alarm in, Audio detection, Motion detection, Trip zone crossing, Video tag
<b>Playback</b>	
<b>Performance</b>	4 Channel HD synchronous playback
<b>Search Modes</b>	Time-lapse, Event log, Motion, Trip-in
<b>Display Zone</b>	4:2 - 4:2
<b>Audio</b>	
<b>HD</b>	1080i@1/2 (up to 3TB capacity for each drive)
<b>Total Capacity</b>	6TB, 3TB & 1.5TB
<b>Video Connections</b>	4x BNC (External Channel 4)
<b>Video In Connections</b>	4x BNC (External IP Camera) x4
<b>Transmission Speed</b>	10Mbps
<b>Camera Power</b>	POE (IEEE 802.3af supported) 4 ports, 50W
<b>Alarm In/Out Lines</b>	10S (Alarm), 10S (In)
<b>Event Notification</b>	Email, Instant Chat, L-Chat, MP3, Callback to Remote S/N, Push notification (SMS, Mobile, SNS, Twitter)
<b>Two-way Audio</b>	10S Center, 10S Series
<b>Cloud Power</b>	10S Center, 10S Mobile, 10S Web
<b>Audio In/Out</b>	Local (MP3) / 10S x 10S
<b>Alarm In/Out</b>	Local (MP3) / 4:1
<b>Alarm Reset In</b>	IP Camera, 4:1 & 4:1 depending on IP Camera
<b>Local Interface</b>	RS232C (Terminal block)
<b>USB</b>	USB 2.0 x 2
<b>Event Interface</b>	Mouse, IP remote control, Network remote keyboard
<b>IT Tools</b>	
<b>Operating System</b>	Windows 7
<b>NET Dimensions w x x x h</b>	300mm x 420mm x 231mm
<b>Unit Weight</b>	1.6kg (net) / 1.65kg
<b>Shipping Dimensions w x x x h</b>	300mm x 1130mm x 200mm
<b>Shipping Weight</b>	1.6kg (net) / 1.65kg
<b>Working Temperature</b>	0°C ~ 40°C
<b>Operating Humidity</b>	10% ~ 90%
<b>Power Type</b>	DC12V 2.0A (For NVR), DC48V 1.0A (For PSE)
<b>Power Consumption</b>	Max. 2.0W (For NVR), Max. 4.0W (For PSE)
<b>Approval</b>	FCC, CE, RoHS

### CONNECTION DIAGRAM



### DIMENSIONS



## Reviews

There are yet no reviews for this product.

