SND-7061

CÁMARA IP DOMO INTERIOR RES: 3 MEGAPIXELES COMPRESIÓN H.264/MJPEG ILUM. MÍNIMA: 0.4LUX LENTE VF: 3-8.5mm ROI (REGIONES DE INTERÉS) IVA: ANTI-MANIPULACIÓN 12V DC / POE

Rating: Not Rated Yet
Ask a question about this product

Manufacturer: SAMSUNG

Description

SND-7061

Onvif

3Megapixel Network Dome Camera

NETWORK CAMERA

Key Features

- Max. 3M (2048 x 1536) resolution
- 16 : 9 Full HD (1080p) resolution support
- 3 ~ 8.5mm (2.8x) varifocal lens
- H.264, MJPEG dual codec
- Multiple streaming
- Smart compression (ROI encoding)
- Tampering, PoE

Dimensions

Unit : mm (inch)

	SND-7061N/P
VIDEO	
Imaging Device	1/2.8" 3M CMOS
Total Pixels	3.14Mp x 1.648(H)
Effective Pixels	2.29Mp x 1.287(H)
Scanning System	Progressive
Min. Illumination	0.4Lux @ F1.2 , 0.08(B), 0.0007Lux (Same up 60x)
Video Output	CVBS : 1.0Vpp / 75Ω composite, 704 x 480(N), 704 x 576(P), for installation
LENS	
Focal Length (Zoom Ratio)	3 ~ 8.5mm (2.8x) varifocal
Max. Aperture Ratio	F1.2
Angular Field of View	H : 96°(Wide) ~ 35.3°(Tele) / V : 70.2°(Wide) ~ 27.5°(Tele)
Min. Object Distance	0.5m (1.64ft)
Focus Control	Manual
Lens Type	DC auto iris
Mount Type	Dome in type
PAN / TILT / ROTATE	
Pan Range	0° ~ 355.5°
Tilt Range	17° ~ 90°
Rotate Range	0° ~ 355.5°
OPERATIONAL	
Camera Title	Off / On (Displayed up to 15 characters)
Day & Night	Auto (Electrical) / Color / B/W
Backlight Compensation	Off / BLC
Digital Noise Reduction	2DNR (Off / On)
Motion Detection	Off / On (4 programmable zones, 3M 15fps, 2M 20fps)
Privacy Masking	Off / On (12 rectangular zones)
Sens-up (Frame Integration)	Off / Auto (2x ~ 60x)
Gain Control	Off / Low / Medium / High
White Balance	ATW / AWC / Manual / Indoor / Outdoor
Electronic Shutter Speed	Auto / A.FLK / Manual (1/30 ~ 1/2,000sec)
Flip / Mirror	Off / On
Intelligent Video Analytics	Tampering (3M 15fps, 2M 20fps)
Alarm I/O	Input: 1ea
NETWORK	
Ethernet	RJ-45 (10/100BASE-T)
Video Compression Format	H.264, MJPEG
Resolution	2048 x 1536, 1920 x 1080P (Full HD), 1600 x 1200, 1280 x 1024, 1280 x 960, 1280 x 720P (HD), 1024 x 768, 800 x 600, 800 x 450, 640 x 480, 640 x 360, 320 x 240, 320 x 180
Max. Framerate	H.264 : Max. 20fps@2048 x 1536, Max. 30fps@the other resolutions MJPEG : 800 x 600 ~ 320 x 180 - 20fps@2048 x 1536, 30fps@the other resolutions 1280 x 1024 ~ 1920 x 1080 - 15 fps@the other resolutions 20 fps x 1536 ~ 1080p@30 fps x 1536
Smart Codec	Yes (Area based method)
Video Quality Adjustment	H.264 : Compression level, Target bitrate level control MJPEG : Quality level control
Bitrate Control Method	H.264 : CBR or VBR, MJPEG : VBR
Streaming Capability	Multiple streaming (Up to 5 profiles)
IP	IPv4, IPv6
Protocol	TCP/IP, UDP/IP, RTP(UDP), RTP(TCP), RTSP, NTP, HTTP, HTTPS, SSL, DHCP, PPPoE FTP, SMTP, ICMP, IGMP, SNMPv1/v2c/v3(MIB-2), ARP, DNS, DDNS, QoS
Security	HTTP(SSL), login authentication, Digest login authentication IP address filtering, User access log, 802.1x authentication
Streaming Method	Unicast / Multicast
Max. User Access	10 users at unicast mode
ONVIF Conformance	Yes (Profile S)
Webpage Language	English, French, German, Spanish, Italian, Chinese, Korean, Russian, Japanese, Swedish, Danish, Portuguese, Turkish, Polish, Czech, Romanian, Serbian, Dutch, Croatian, Hungarian, Greek, Norwegian, Finnish
Web Viewer	Supported OS : Windows XP / VISTA / 7, MAC OS 10.7 or higher Supported Browser : Internet Explorer 7.0 or higher, Firefox 9 or higher, Google Chrome 15 or higher, Apple Safari 5.1 or higher
Central Management Software	SmartViewer
ENVIRONMENTAL	
Operating Temperature / Humidity	-10°C ~ +55°C (+14°F ~ +131°F) / Less than 90% RH
Storage Temperature / Humidity	-20°C ~ +60°C (-22°F ~ +140°F) / Less than 95% RH
ELECTRICAL	
Input Voltage / Current	12V DC, PoE (IEEE802.3af)
Power Consumption	Max. 3.7W (12V DC), Max. 4.7W (PoE)
MECHANICAL	
Color / Material	Ivory / Plastic
Dimensions (WxHxD)	Ø115.6 x Ø2.7mm (Ø4.56" x 3.65")
Weight	345g (0.76 lb)

SAMSUNG TECHWIN

Reviews

There are yet no reviews for this product.